



Floorcoverings of Marin County, Inc		WOCA OUTDOOR PRODUCTS		
1607 Fourth Street				
San Rafael California 94901				
Tel: 800 544 7721		July 1, 2010		
Fax: 415 453 1245				
Email: <a href="mailto:floorsofmarin@sbcglobal.net">floorsofmarin@sbcglobal.net</a>				
Website's: <a href="http://www.wocaoil.com">www.wocaoil.com</a> / <a href="http://www.floorsofmarin.com">www.floorsofmarin.com</a> / <a href="http://www.floorcoveringsofmarin.com">www.floorcoveringsofmarin.com</a>				
OUTDOOR PRODUCTS		0.75 liter	1.0 liter	2.5 liter
Wood Quick (for light cleaning) <b>Coverage = 60-100 sq.ft./liter (1 to 5 mix with water)</b>			26.45	
Decking Cleaner (for heavy cleaning) <b>Coverage = 60-100 sq.ft./liter (1 to 2 mix with water or for extreme dirt use undiluted)</b>				54.30
Furniture Oil Natural <b>Coverage = 120-160 sq.ft./liter</b>		34.30		92.15
Decking Oil Waterbased, Natural <b>Coverage = 100-150 sq.ft./liter</b>				105.75
Decking Oil Waterbased, Teak, Grey, Walnut, Anthracite, Larch <b>Coverage = 100-150 sq.ft./liter</b>				115.75
Decking Oil Waterbased, Black <b>Coverage = 100-150 sq.ft./liter</b>				134.30
Outdoor Wood Oil for decking, siding & furniture:				
Natural		29.30		69.30
Cedar, Nutbrown, Olive, Oak, Cherry		44.30		87.90
Pine, Spruce, Larch, Silver, White		44.30		87.90
<b>Coverage = 150-200 sq.ft./liter</b>				
Brush I (for cleaning all decks before oiling)				
Brush II (for secondary cleaning of all decks before oiling)				
Application Brush (for waterbased Decking Oil)				
<b>Application Instructions for waterbased WOCA Decking Oil :</b>				
1. <i>Hose down the deck with plenty of water.</i>				
2. <i>Mix Decking Cleaner with water in solution 1 to 2. (For extremely dirty decks, use undiluted.) Spray or brush the solution onto the deck and leave it for 5 minutes.</i>				
3. <i>Using Brush I with a floor buffer, scrub dirt, stains, old finish, and oxidation away. Tough stains may require more solution and additional scrubbing. The edges are scrubbed using a medium stiff nylon brush.</i>				
4. <i>Hose all residue off the deck with water.</i>				
5. <i>Using Brush II with the floor buffer, scrub off any remnants still on the deck.</i>				
6. <i>Hose off the deck with water. Leave deck to dry at least 24 hours.</i>				
7. <i>Using the Application Brush, apply waterbased Decking Oil first between all the decking boards and then on the deck. Let sit 20 - 30 minutes.</i>				
8. <i>Polish the Decking Oil into the wood decking with a floor buffer using a red or yellow pad. Polish to complete saturation.</i>				
9. <i>Polish off all excess oil using a cloth under the buffer.</i>				
10. <i>You are done! In order to retain maximum protection and beauty, it is recommended to re-oil the deck once a year.</i>				